

CREATING A CLEANER, SAFER, HEALTHIER WORLD.



M30

LARGE INTEGRATED SWEEPER-SCRUBBER

- Effectively clean in just one pass wet or dry with FloorSmart® integrated cleaning system technology
- Achieve excellent cleaning results with ec-H2OTM technology and MaxPro^{2TM} hydraulic technology
- Increase visibility with cab-forward design, open sightlines, and steering-wheel-mounted controls
- Improve operator and supervisor experience with available Pro-Panel[™] technology

AN INNOVATIVE, HIGH-PERFORMANCE, INTEGRATED SWEEPER-SCRUBBER FOCUSED ON DELIVERING CUSTOMISED SOLUTIONS TO MEET CUSTOMER NEEDS



THE M30 ADDRESSES YOUR KEY BUSINESS CHALLENGES



REDUCE COST TO CLEAN

• Improve productivity by cleaning in a single pass with FloorSmart® integrated cleaning system technology that combines sweeping and scrubbing functions.



MAINTAIN HEALTH & SAFETY

• Ensure employee safety with a high-capacity, multi-level hydraulic rear hopper that eliminates the need to manually handle debris.



ENHANCE FACILITY IMAGE

• Deliver excellent cleaning results with MaxPro2[™] hydraulic technology that provides consistent power to the brush drive motors regardless of floor surface changes.



EASY OPERATION & MAINTENANCE

Reduce training and simplify operation with the Touch-n-Go[™] control module featuring 1-Step[™] start button.

MINSIDE THE MINSID

Touch-n-Go[™] control module with 1-Step[™] start button allows easy access to all settings without having to remove hands from the wheel

Full front shroud ensures operator leg and foot protection

Corrosion-resistant •••• Duramer™ construction on shrouding and solution and recovery tanks for long life

Front-wheel steering and high-traction tyres provide excellent manoeuvrability in congested spaces Forward operating position improves operator safety

and visibility

Optional ec-H2O[™] technology improves productivity and reduces environmental impact


Solution and recovery tanks allow for complete visual inspection and cleanout :

Heavy-gauge steel frame with full wraparound bumper and cushioned rollers help protect machine life •

Yellow touch points save time and ensure proper maintenance

Dura-Track[™] parabolic squeegee with SmartRelease[™] improves water pickup and damage resistance

Rugged 18 in/460 mm tyres allow easy manoeuvring indoors and out



Wet/dry synthetic fibre panel filter with InstantAccess™ provides excellent dust control and shakeback

Scrubbing side brush widens cleaning path up to 54 in/1,370 mm.

Spray hose makes machine spraydown and cleanup quick and easy.

Rear and side steel guards protect squeegee upon impact and prevent it from hooking on to obstacles









ENGINEERED FOR PRODUCTIVITY



Hydraulic Rear Hopper

- Touch-n-Go[™] control module with 1-Step[™] start button allows operators quick access to all settings without removing hands from the steering wheel.
- High-capacity, multi-level hydraulic rear hopper (3.9 ft³/110 | | 390 lbs/177 kg) increases cleaning productivity by eliminating the need to manually handle debris.





- Cab-forward position and spacious operator compartment provide outstanding visibility, safety and ergonomics to protect operators, the machine and your facility.
- Easy-to-identify yellow maintenance touch points help save time and money in routine maintenance activity.



Easy-Access Design



Yellow Maintenance Touch Points

Overhead guard protects operators from falling objects.

Dura-Track™ Parabolic Squeegee

High-powered pressure washer allows for easy blast-cleaning of hard-to-reach areas.

Safety warning light ensures awareness of machine during operation.







INNOVATIVE TECHNOLOGIES



AVAILABLE PRO-PANEL™ TECHNOLOGY REDEFINES THE USER EXPERIENCE

Transform your cleaning operation with Pro-PanelTM technology – a revolutionary breakthrough in user experience. Pro-PanelTM technology integrates multiple controls into an intuitive, high-visibility touchscreen interface.



- Effectively manage your asset and operators with supervisor controls that allow the machine function to be matched to the operator skill level and prevent unauthorised use.
- Ensure successful starts with Pro-IDTM operator login, which automatically activates the specific operator's personalised cleaning settings and downloadable Pro-CheckTM pre-operation checklists.
- Increase cleaning efficiency with programmable Zone Settings™ that allow you to establish preferred cleaning settings by area of facility.
- Provide operators a view of their cleaning path without having to take their eyes off the direction of travel with **PerformanceView** TM .
- Increase visibility with a backup camera featuring coloured guidelines that help drivers safely dump debris and avoid objects when in reverse.
- Reduce the need for extensive operator training with on-board, on-demand videos.
- Increase machine ease of use with **28 different language** options.

ADDITIONAL EXCLUSIVE TECHNOLOGIES

All technologies increase scrub time up to three times using a single tank of water.



ec-H2O[™] technology electrically converts water into an innovative cleaning solution that cleans effectively, saves money, improves safety, and reduces environmental impact* compared to daily cleaning floor chemicals and methods.







^{*} Based on a study by EcoForm™. Visit www.tennantco.com for more information.



ES® Extended Scrubbing productivity enhancement system recycles cleaning chemicals to increase uptime and improve productivity by scrubbing floors using 66% less chemicals than traditional cleaning methods.

ENVIRONMENTAL STEWARDSHIP



ec-H2O and FaST technologies are NFSI (National Floor Safety Institute) Certified. NFSI certification ensures a product has passed a two-phase testing process, proving the floor product helps to reduce potential for slip-and-fall accidents.



ec-H2O and FaST technologies are registered by NSF International. NSF International is an independent, not-for-profit organisation that ensures formulation and labels on these products meet appropriate food safety regulations.



Tennant FaST 365 and FaST 965 detergents have been awarded the European Eco-label.

This proves that our Tennant FaST® detergents have a reduced environmental impact compared to standard detergents.



ec-H2O technology won the European Business Award 2009 for the Business Innovation of the Year, one of the most prestigious business awards. The European Business Awards (www.businessawardseurope.com) is an independent awards programme designed to recognise and promote excellence, best practice and innovation in the European business community.













Safety

Manage your cleaning programme with key performance metrics based on machine data.

GENUINE TENNANT PARTS, SUPPLIES AND SERVICE

Tennant Service Offering

- Maximise safety, productivity and uptime
- Control and protect your investment and lower your total cost of ownership
- Benefit from over 200 factory-trained service technicians across Europe

Tennant Parts & Supplies

- Operate your machine with confidence
- Benefit from years of worry-free operation

Tennant Cleaning Solutions

- Further your sustainable cleaning goals
- Choose sustainable benefits your company wants

M30 LARGE INTEGRATED SWEEPER-SCRUBBER

INTEGRATED CLEANING SYSTEM

48 in/1,220 mm Cleaning path With scrubbing side brush 62 in/1,575 mm With sweeping side brush 64 in/1,625 mm Cylindrical main brushes Brush speed 480 rpm Brush down pressure (up to) 390 lb/177 kg Brush diameter (2) 12 in/305 mm Side brush Brush speed 150 rpm Scrubbing brush diameter 16 in/410 mm Sweeping brush diameter 21 in/533 mm Tanks Solution tank 75 gal/284 l Solution capacity with ES® 100 gal/379 l

95 gal/360 l Recovery tank Demisting chamber 20 gal/76 l Debris hopper Volume capacity 7 ft³/198 I Weight capacity 650 lb/295 kg Dump height (variable to) 60 in/1,525 mm

Vacuum fans Scrubbing fan speed 11,000 rpm 35 in/890 mm Scrubbing fan water lift Sweeping fan speed 6,500 rpm Sweeping fan airflow 290 cfm/8.2 m3/min

PROPELLING SYSTEM

Propel speed forward (variable to) 8 mph/13 km/h Propel speed reverse (variable to) Engine-LPG (2.0L) 3 mph/4.8 km/h **Gross Intermittent Power***

38.5 kW (51.6 Hp) @2800 rpm Tennant Governed Power 31.6 kW (42.4 Hp) @2300 rpm Engine-diesel (1.5L) **Gross Intermittent Power***

33.0 kW (44.2 Hp) @3000 rpm Tennant Governed Power 30.6 kW (41.0 Hp) @2800 rpm Gradeability

Transport at gross weight 8.0°/14% 6.0°/10% Working (cleaning) Ground clearance (transport) 3 in/80 mm

DUST CONTROL SYSTEM

Synthetic fibre panel Filter system 78 ft²/7.3 m² Filter area 3 microns @ 99% efficiency Dust filtration (to) Timed, beater bar Shaker mechanism (automatic)

MACHINE SPECIFICATIONS

Length 108 in/2,745 mm Width Frame 58 in/1,473 mm 59 in/1,500 mm Rear squeegee With side brush 64 in/1,625 mm Height 58 in/1,473 mm With overhead guard 84 in/2,135 mm Weight (empty) 4,000 lb/1,815 kg Minimum aisle turn 125 in/3,175 mm

WARRANTY

See your local representative for warranty information.

* Per SAE J1995

Specifications subject to change without notice.

SEEING IS BELIEVING

For a demonstration or additional information contact us:

TENNANT UK CLEANING SOLUTIONS LTD

0800 111 4402 (local rate UK only) 01604 583191



sales.uk@tennantco.com enquiries@tennantco.com

